



# MATERIAL SAFETY DATA SHEET

# Prepared in accordance with ISO 11014-1/ ANSI standard Z400.1-2004

Revision Date: 11/1/2010 MSDS No.: ND4068

#### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name: 330 Metal Bonding Superglue For Close Fitting Parts** 

Synonyms: Superglue

Use of the Substance/Preparation: Adhesive

Supplier:

ND Industries, Inc. 1893 Barrett Road Troy, Michigan 48084 Tel: (248) 288-0000 Fax: 248) 288-0022

Emergency Telephone Number: 24 hr. EMERGENCY CHEMTREC

1-800-424-9300

#### 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW-**Clear liquid, with sharp irritating odor. Cyanoacrylate adhesives are a very fast setting and strong adhesive. It

bonds human tissue and skin in seconds. Avoid contact

with skin and eyes. Avoid breathing vapors.

**Principle Routes of Exposure:** Skin, eyes and inhalation.

**POTENTIAL HEALTH EFFECTS:** 

Eye Contact: Irritating to eyes. Causes excessive tearing. Eyelids may

bond.

**Skin Contact:** Bonds to skin in seconds. May cause skin irritation.

Cyanoacrylates have been reported to cause allergic reaction but due to rapid polymerization at the skin surface, an allergic response is rare. Cyanoacrylates generate heat during the cure process and, in rare

instances; a large drop can burn the skin.

**Inhalation:** Exposure to vapors above the established exposure limit

results in respiratory irritation which may lead to difficulty

breathing and tightness in the chest.

**Ingestion:** Material is not harmful if ingested. Cyanoacrylates are

almost impossible to swallow because they solidify in the

mouth.

Carcinogenic Effects: No data available on the product itself. Contains no

known carcinogens.

ND Industries, Inc.

Page 2 of 6 Product Name: Metal Bonding Superglue Product Code: 330 Revision Date: 11/1/2010

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	EINECS Number	Weight %	EU Classification
Ethyl-2 Cyanoacrylate	7085-85-0		80-95	
Poly Methyl Methacrylate	9011-14-7		5-10	

## 4. FIRST AID MEASURES

**Skin Contact:** Soak in warm water. Do not pull skin apart.

**Eye Contact:** Flush with warm water. If eye lids are bonded closed, release

eyelashes with warm water by covering the eye with a wet

pad. Do not force eye open.

Inhalation: Remove to fresh air. If symptoms persist, obtain medical

attention.

Ingestion is unlikely. If lips are accidentally stuck together Ingestion:

> apply lots of warm water and encourage maximum wetting and pressure from saliva inside the mouth. Peal or roll lips apart. Do not try to pull the lips with direct opposing action. It is almost impossible to swallow Cyanoacrylate. The adhesive

solidifies and adheres in the mouth. Saliva will lift the

adhesive in one to two days.

Cyanoacrylate adhesive is a very fast setting and strong **Notes to Physician:** 

adhesive. It bonds human tissue and skin in seconds. Experience has shown that accidents due to Cyanoacrylates

are best handled by passive, non-surgical first aid.

## 5. FIRE AND IGNITION INFORMATION

**Flash Point** 150-200°F, Tag Closed Cup

**Explosion Limits in Air – Upper (%):** Not established. Explosion Limits in Air - Lower (%): Not established. **OSHA Flammability Classification:** Combustible. **Auto-ignition Temperature:** Not established.

**Extinguishing Media:** Foam, Dry Chemical or Carbon Dioxide

**Special Protective Equipment for** 

Firefighters: Fire fighters should wear full turnout gear including self-

contained breathing apparatus operated in positive pressure

mode.

None. **Specific Hazards:** 

Hazardous Decomposition and/or

**Combustion Products:** Trace amounts of toxic and/or irritating fumes may be

released under fire conditions.

**Risk of Dust Explosion:** Not applicable.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Only trained personnel should clean a spill. Make sure spill area is

well ventilated. Use adequate personal protective equipment.

**Methods for Cleaning Up:** Do not use cloths for clean-up. Flood spilled material with water to

polymerize. Cured material can be scraped up and disposed of as

non-hazardous waste.

ND Industries, Inc.

Product Name: Metal Bonding Superglue Product Code: 330 Revision Date: 11/1/2010

#### 7. HANDLING AND STORAGE

**Handling:** Avoid contact with skin, eyes, and clothing. Avoid breathing vapor or

mist. Avoid contact with paper goods or fabric. Contact with these materials may cause rapid polymerization which can generate smoke

Page 3 of 6

and strong irritating vapors.

**Storage:** Store away from heat and direct sunlight to maximize shelf life.

Store inside in a dry location. Keep container tightly closed.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

## **EXPOSURE LIMITS**

Exposure limits for those components with limits are stated below.

Ethyl-2 Cyanoacrylate: US OSHA PEL: None

USACGIH - TLV: 0.2 ppm TWA

Poly Methyl Methacrylate: US OSHA PEL: None

US ACGIH - TLV: None

PEL: Permissible Exposure Limit STEL: Short Term Exposure Limit TLV: Threshold Limit Value TWA: Time Weighted Average

US ACGIH: United States American Conference of Governmental Industrial Hygienists

US OSHA: United States Occupational Safety and Health Administration

ENGINEERING CONTROLS Local exhaust ventilation is recommended to maintain vapor level

below TLV.

#### PERSONAL PROTECTIVE EQUIPMENT

**Respiratory Protection:** Not applicable with good local exhaust. Use NIOSH approved

respirator if there is a potential to exceed exposure limits.

**Hand Protection:** Polyethylene or non reactive gloves. Do not use cotton, PVC,

nylon or wool.

**Eye Protection:** Safety glasses or goggles with side shields.

**Skin and Body Protection:** Wear chemical resistant clothing when potential for skin contact

exists.

Other: Eyewash and safety shower should be available for use in the

immediate work area. Wash hands after using and before

eating, drinking, smoking or using the lavatory.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:Clear liquid.Odor:Sharp, irritating.pHNot applicable.

Vapor Pressure: Less than 0.2mm Hg @25°C

**Boiling Point/Range:**Greater than 300°F
Melting Point/Range:
Not applicable.

Water Solubility: Negligible, Polymerized by water.

Specific Gravity: 1.06 at 20° C

ND Industries, Inc. Page 4 of 6

Product Name: Metal Bonding Superglue Product Code: 330 Revision Date: 11/1/2010

**% Volatile** (SCQAMD Method 316B): less than 20 grams per liter, 2% (estimated)

**Evaporation Rate:**Partition Coefficient (n-octanol/water):
Not applicable.
Not established.

#### 10. STABILITY AND REACTIVITY

**Stability:** Stable under recommended storage conditions.

Hazardous Polymerization: Rapid exothermic polymerization will occur in the presence of

water, amines, alkalis and alcohols.

Mechanical Sensitivity (shock): Not applicable.

**Conditions to Avoid:** Polymerized by contact with water, alcohols, amines, and

alkalis.

**Hazardous Decomposition and/or** 

Combustion Products: Not established.

#### 11. TOXICOLOGICAL INFORMATION

#### **ACUTE TOXICITY**

Oral LD50: Acute oral LD50 >5000mg/kg (rat) (estimated).

**Inhalation LC50:** Not established.

**Dermal LC50:** Acute dermal LD50> 2000 mg/kg (rabbit) (estimated).

**Eye Irritation:** Not established. **Skin Irritation:** Not established.

## **CHRONIC TOXICITY**

Carcinogenic Effects: No data available on the product itself.

Mutagenic Effects: No data available on the product itself.

Reproductive Toxicity: No data available on the product itself.

Sensitizing Effects: No data available on the product itself.

Synergistic Materials: No data available on the product itself.

## 12. ECOLOGICAL INFORMATION

Information given is based on data on the components and the toxicology of similar products.

**Aquatic Toxicity:** No data available on the product itself.

## **EVIRONMENTAL FATE**

Mobility:No data available on the product itself.Bioaccumulation:No data available on the product itself.Persistence / Degradability:No data available on the product itself.

**Distribution to Environmental** 

**Compartments:** No data available on the product itself.

#### 13. DISPOSAL CONSIDERATIONS

**Disclaimer:** Information in this section pertains to the product as shipped in its intended composition as described in Section 2 of this MSDS. Contamination or processing may change waste characteristics and requirements. Regulations may also apply to empty containers, liners or rinsate. State/provincial and local regulations may be different from federal regulations.

RCRA Classification (40 CFR 261): Dispose of in accordance with all local, state, and federal

Page 5 of 6 Product Name: Metal Bonding Superglue Product Code: 330 Revision Date: 11/1/2010

regulatory requirements.

#### 14. TRANSPORTATION INFORMATION

CFR:

Proper shipping name: Combustible liquid, n.o.s. (more than 450 liters)

Hazard class or division: Combustible liquid (more than 450 liters)

Identification number: NA 1993 (More than 450 liters) Exceptions: Unrestricted under 450 liters

Marine pollutant: Nο

## 15. REGULATORY INFORMATION

#### **Hazard Classification**

United States - OSHA (29 CFR 1910.1200): This product is considered hazardous under OSHA. Canada - WHMIS Classification (CPR, SOR/88-66): B.3, D.2.B

#### **International Inventories**

All components of this product are listed on or exempt from the following inventories:

- Domestic Substances List (DSL) (yes)

- United States Toxic Substances Control Act (TSCA) Inventory (yes)

## **U.S. Federal Regulations**

Clean Air Act amendments of 1990 (CAA, Section 11240: CFR 82): Contains no hazardous air pollutants.

Clean Water Act (CWA, 40 CFR 116): Contains no priority pollutants.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA, 40 CFR **302):** None.

#### Superfund Amendments and Reauthorization Act, Title III (SARA):

SARA Section 302 (40 CFR 355) Extremely Hazardous Substances: None.

SARA Section 311/312 (40 CFR 370) Hazard Category: Immediate health hazard, Delayed health hazard, Fire, Reactive

SARA Section 313 (40 CFR 372) Toxics Release Inventory: None.

## **U.S. State Regulations**

California Proposition 65: None.

#### **16. OTHER INFORMATION**

#### **HMIS Rating**

HMIS Index: \*- chronic, 0 - Minimal, 1 - slight, 2- moderate, 3 - serious, 4 - severe

Health: 2 Flammability: 2 Physical Hazard: 1

#### **Additional Contacts:**

ND Industries, Inc.

Page 6 of 6

Product Name: Metal Bonding Superglue Product Code: 330 Revision Date: 11/1/2010

**Prepared by:** ND Industries, Inc. – Safety, Health and Environmental Affaires

Revision Date: n/a
Previous Revision Date: n/a
Reasons for Revision: n/a

#### Disclaimer:

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

®ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated,
™ Vibra-TITE is a trademark of ND Industries, Inc.